

PUCK

ARKOSLIGHT®



					W	K	UGR	Lm	%Eff
PUCK	A251-10-01-	WT	NT	ZT	11W	3000K	11,1	825	94%
	A251-10-02-	WT	NT	ZT	11W	4000K	11,6	950	94%










CRI>80

 INCL | ELEC

 >36000

 50°





L70B50 (6K)

COLOUR | WT  | NT  | ZT 

MATERIAL |  AL |  OPTICAL GLASS |

 0,40 Kg

 115x105x62 mm



PUCK 3000 K

LED 50° 3000 K		11 W			
C90 - C270		h	d	E _{med}	E _{max}
		(m)	(m)	(lux)	(lux)
	CIE η L: 0.94 95-98-99-100-94 DIN A60 UTE 0.94A CIBSE BZ 1	1	0.92	704	1058
		2	1.84	176	264
		3	2.76	78	117
		4	3.69	44	66

PUCK 4000 K

LED 50° 4000 K		11 W			
C90 - C270		h	d	E _{med}	E _{max}
		(m)	(m)	(lux)	(lux)
	CIE η L: 0.94 95-98-99-100-94 DIN A60 UTE 0.94A CIBSE BZ 1	1	0.92	811	1219
		2	1.84	202	304
		3	2.76	90	135
		4	3.69	50	76

⌚ L70B50 (6K)